



DIMENSIONS IN MM

COLLET CHUCK DESIGNATION	SUITABLE FOR COLLET	COLLET MAX TAP SIZE	D	LI	L	NUT DESIGNATION	SPANNER DESIGNATION	FIG REF
CTTC22/RD16/100F	RD16	M10	22	100	151	UM/RD16	GS25	1
TCCT22/RD16/100	RD16	M10	22	100	135	UM/RD16	GS25	2
TCCT3/4"/RD16M/65	RD16	M10	19.05	65	103	UM/RD16M	E-16M	2

NOTE :

- 'TAPER' TAPPING COLLET CHUCK ARE ALSO AVAILABLE ON REQUEST.
- PLACE SEPERATE ORDER FOR SPANNERS.
- SUITABLE FOR TAPPING M3 TO M10
- COLLETS RD16 OF DIFFERENT BORES CAN BE INTERCHANGED TO THE SHANK DIA OF TAP.
- COMPRESSION & TENSION ENSURE BETTER THREAD FORM AND ACCURACY ON JOB.
- SUITABLE ONLY ON CNC MACHINES AND ON OTHER MACHINES HAVING AUTO REVERSING FACILITY.
- BEST SUITED FOR SOFT MATERIALS.
- CAN BE USED ON A COLLET CHUCK OR ON A SIDELOCK HOLDER.
- TENSION TYPE TAPPING CHUCK ENSURES CONSISTANCY IN TAPPING LENGTH.
- NUT IS SUPPLIED ALONG WITH TAPPING COLLET CHUCK.
- CAN BE SUPPLIED IN INCH SIZES ALSO AS REQUIRED BY THE CUSTOMER.

ORDERING INSTRUCTION

CTTC 22/RD16/100



ORDERING INSTRUCTION

TCCT 22/RD16/100

